



- C1:VCC
- C2:RST
- C3:CLK
- C4:RESERVED
- C5:GND
- C6:VPP
- C7:I/O
- C8:RESERVED

SIM pin assignment	
PIN#	Name
C1	VCC
C2	RST
C3	CLK
C4	RESERVED
C5	GND
C6	VPP
C7	I/O

Specification

MATERIAL:

Insulator: High Temperature Thermoplastic, UL 94V-0.
 Contact: Copper Alloy
 Shell: SUS

PLATING:

Contact: Plated 50u'' Ni Overall Contact Au 1U
 Shell: Plated 50u'' Ni Overall
 Plated 1u''Au Selective Contact Area

Electrical:

Current Rating :0.5mA AC/DC max.
 Voltage Rating :125V AC/DC
 Ambient Temperature Range :-20° C~+60° C
 Storage Temperature Range :-40° C~+70° C
 Ambient Humidity Range :95% R.H. Max.
 Contact Resistance:100mΩ max.
 Insulation Resistance:1000MΩ min./500VDC
 Peak temperature: 260° C±5° C
 Mating Cycles:5,000-10,000 Insertions

6 Pin Push Push Micro Sim Card Holder Type 1

REVISION NO.	ECR NO.	DESCRIPTION	MARK	DATE
1				
2				
3				
4				
5				
6				